



TAPPAN WIRE & CABLE ANNOUNCES:

"A NEW and IMPROVED VFD CABLE"

APPROVALS & FEATURES	COMPETITION	TAPPAN
UL STANDARD 1277, TYPE TC-ER, 90°C, 600V, SUN RES, DIR. BUR.	X	X
UL 1000 VOLT FLEXIBLE MOTOR SUPPLY CABLE	X	X
85% TINNED COPPER BRAID SHIELD & FOIL SHIELD 100% COVERAGE	NOT ALL	X
XLP INSULATION, 14 & 12 AWG (RHW-2), 10 - 2 AWG (XHHW-2)	X	X
FLAME TESTS: UL 1581 VERTICAL TRAY, IEEE 1202, CSA c(UL) FT-4	X	X
CSA AWM I/II A/B XHHW-2 - RHW-2	X	X
VERY FLEXIBLE TINNED COPPER CONDUCTORS	NOT ALL	X
OIL RESISTANT - UL OIL I & II	NONE LISTED	X
TEMPERATURE RANGE: -25°C TO +90°C	X	X
-40°C UL COLD BEND	NONE LISTED	X
CLASS I & II DIVISION 2 HAZARDOUS LOCATIONS	X	X
RoHS	X	X
CE	X	X

Compare our cable to what your are currently buying. Tappan's VFD Cable offers: Flexibility, UL Oil I & II, -40°C Cold Bend Test, WTTC, (Wind Turbine Tray Cable requirement) - *all at a competitive price*



**CALL US TODAY FOR
A SAMPLE &
MORE INFORMATION**



EXPLORE OUR CABLE-BILITIES®™

Please call your Tappan Sales Representative @ **1-800-WIRE-911** (1-800-947-3911) or visit our Website www.tappanwire.com.